



Description				
Joystick Type SK 60-0240E				
Number of axis	2-axis, x- and y-axis			
Operation by	Handle 48-203 (sealed)			
Crossguide	light			
Center tab	-			
Retaining spring	strong Z-Nr. 50-116			
Switch function	3-1-3 per axis			
Switchcontact α	$\pm 3.333'$			
Notches	7 per axis			
Electrical characteristics				
Resistance value				
Power disipation				
Contact rating	Zero potential difference between segments 5 V DC, 5mA			
Type of switch				
Operating voltage	max. 30V DC			
Axis	Potentiometer side	Connector side		
	Direction	Colour/Number		
x-Axis	↑ +x	47	44	open
		46		-
	↓ -x	45		closed
		48		open
y-Axis	↑ +y	43	34	-
		42		closed
	↓ -y	41		open
		37		-
Handle with push-button switch				
Switch	contact			
	open			
	closed			

		Oberfläche	Maßstab 1:1	Position	Menge
		Datum	Name		
		Bearb. 11.03.98	DM	Joystick	
		Gepr.			
		Norm			
d	mit runden Stützen	27.01.11	MK		
c	new Layout	13.10.04	TZ		
b	Text chanced	16.10.01			
a	measure 6.3 was 5	14.01.99	DM		
Zust.	Änderungen	Datum	Name		
			Dateiname: E:\DWG SK60\60-0240E.dwg	60-0240E d	
				Blatt -	Bl

GENGE & THOMA AG
 OH-2543 Lengnau/Bliz